

# M100 Series

# maestro



empowering wireless

## Compact & intelligent industrial modem

The M100 is the perfect solution for M2M applications facing tough environmental conditions and extended lifetime requirements. This compact and intelligent modem running Open AT<sup>®</sup> Application Framework supports specific protocols and accessories specifically developed by Maestro to ease integration with industrial equipment such as electricity meters, programmable logic controllers, lifts and vending machines. The M100 is fully type approved in 2G, CDMA or 3G and ready for global deployment.

## M100 Series

### M100 2G

GPRS / EDGE:

- ✓ RS-232
- ✓ Digital input / output x 1
- ✓ Analogue input x 1
- ✓ Gold cap. backed-up RTC

### M100 CDMA<sup>plus</sup>

Verizon Wireless CDMA2000 1X:

- ✓ RS-232
- ✓ Digital input x 2
- ✓ gpsOne
- ✓ USB 2.0

### M100 3G XT

Dual or tri-band HSDPA:

- ✓ RS-232
- ✓ Digital input / output x 2
- ✓ gpsOneXTRA<sup>™</sup>
- ✓ USB 2.0

### Easy Configuration

The Maestro Smart Pack II is pre-loaded in all M100 modems to ease device setup and network registration. This application includes much-needed features for system integrators such as auto baud-rate detection, auto-TCP/UDP connection, self-healing in case of network failure, industry specific protocols and many more.





## Technical specifications

FEATURES	M100 2G	M100 CDMA <sup>plus</sup>	M100 3G XT
<b>CELLULAR TECHNOLOGY</b>			
GSM / GPRS / EDGE	Quadband / class 10 / class 10		Quadband / class 10 / class 12
CDMA2000 1X		✓	
W-CDMA / HSDPA			Up to 3.6 Mbps downlink
Voice / Data / Fax / SMS	✓		✓
Internet services	TCP / UDP / FTP / HTTP / SMTP / POP3 / SNMP / SSL		
<b>LOCATION TECHNOLOGY</b>			
GPS (NMEA port and command)		Standalone, gpsOne™	Standalone, gpsOneXTRA™, A-GPS
GPS Specifications		gpsOne™	A-GPS
Cold start sensitivity (dBm) / TTFF (seconds)		-145 / 39	-153 / < 5
Hot start sensitivity (dBm) / TTFF (seconds)		-158 / 9	-153 / < 3
Tracking sensitivity (dBm)		-160	-155
Accuracy in open sky (meters)		< 3	< 2
<b>FUNCTIONAL FEATURES</b>			
AT command set		> 300	
Sierra Wireless Open AT® Application Framework		✓	
Maestro Wireless Solutions Smart Pack II	Auto baud-rate detection, auto-TCP/UDP, self-healing protocol, DynDNS, etc.		
Download Over The Air		✓	
Autorestore - timer reset		✓	
<b>OTHER FEATURES</b>			
Operating status LED		✓	
Casing		Aluminium alloy	
DIN rail mountable		✓	
<b>INTERFACES</b>			
SIM (V)	1.8 / 3.0		1.8 / 3.0
RS-232C on 15-pin sub-D connector		✓	
USB 2.0 on mini-B female connector (slave only)			✓
Micro-Fit™ 4-pin connector	Power supply (on 2 pins)		
	1 x digital input / output (on 1 pin) 1 x analogue input (on 1 pin)	1 x digital input (on 1 pin) 1 x digital input (on 1 pin)	2 x digital input / output (on 2 pins)
SMA antenna connector (50 Ω)	1 x cellular	1 x cellular and 1 x GPS (passive and active)	1 x cellular and 1 x GPS (passive and active)
<b>DIMENSIONS</b>			
Size without connectors (mm)		62.8 x 60 x 21.8	
Weight (g)		90	
<b>TEMPERATURE RANGE</b>			
Operating (°C)		-40 ~ +85	
Relative humidity (% non-condensing)		0 ~ 95	
<b>POWER SUPPLY</b>			
Input voltage (V DC)		5 to 32	

ORDERING INFORMATION	M1002G	M100CDMAPLUS-V	M1003GXT00	M1003GXT02	M1003GXT04
Frequency bands (MHz)	850/900/1800/1900	800/1900	850/1900	900/2100	800/850/2100
<b>REGULATORY</b>					
CE	✓			✓	✓
FCC		✓	✓		
PTCRB			✓		
A-Tick				✓	✓
<b>CARRIER</b>					
AT&T / Rogers Wireless			✓		
Verizon Wireless		✓			
Telstra					✓
YES Optus				✓	
NTT Docomo					✓

Maestro Wireless Solutions Limited  
9<sup>th</sup> Floor, Wing Cheong Factory Building  
121 King Lam Street, Cheung Sha Wan  
Kowloon, Hong Kong

Tel: +852 3955 0222  
Fax: +852 3568 4833  
www.maestro-wireless.com  
contact@maestro-wireless.com

Copyright Maestro Wireless Solutions Limited. | Version 1.2. | We reserve the right at any time and without prior notice to modify or improve the devices and the services offered. | The same applies to the accessories which could also be withdrawn.

